

UV-UHO-B2D-M3F3D

Uniarch



Features

- Uniarch
- Panda B Series
- WIFI Bullet IP Camera
- High image quality with 1/3" CMOS sensor and F1.6 aperture
- 3MP (2304x1296)@30/25fps
- Ultra 265, H.265, H.264, MJPEG
- Built-in microphone and speaker
- Intelligent IR: Range up to 20 m
- 3 axis
- White light: Range up to 10 m
- Dual Light Mode: Changes between infrared and white light automatically when preset is activated.
- Human and vehicle detection
- Supports Micro SD card of 128GB
- Wi-Fi connection and easy installation
- Protection IP67

Specifications

Brand	Uniarch
Image sensor	1/3" Progressive Scan CMOS
Maximum resolution	3 Megapixel (2880x1620)
Lens	2.8 mm
Main Stream rate	3MP (2304*1296) , Max 25fps; 1080P (1920*1080), Max 30fps; 720P (1280*720), Max 30fps
Extra Stream rate	640*360,Max 30fps; 2CIF(704*288), Max 30fps; CIF(352*288), Max 30fps;
Range performance	46.7 (D), 18.7 (O), 9.3 (R), 4.7 (I)
Compression	Ultra 265, H.265, H.264, MJPEG
Minimum illumination	Colour: 0.003 lux (F2.1 AGC ON) 0 lux with IR on
Infrared range	20 m
White light range	10 m
Image improvements	DWDR, BLC, HLC, AGC, 2D/3D-NR, Motion detection, ROI, Privacy Mask
Day / Night	Mechanical ICR filter
Internal memory	MicroSD card slot, Max 128 GB
Alarms	Does not have
Audio	Built-in microphone and speaker
Detection functions	Motion Detection, Ultra Motion Detection, Audio Detection, Tamper Alarm.
Wi-Fi	IEEE802.11b/g/n
WI-FI frequency range	2.4 GHz ~ 2.4835 GHz
Remote access	Web Browser, CMS Software (EZStation), Smartphone (EZView/EZLive)
Power	DC 12V / 5.7W
Temp. operation	-30° C ~ 60° C
Degree of protection	Weatherproof IP67
Dimensions	148 (H) x 78 (W) x 78 (D) mm

Weight

310 g
