

UV-UHO-S3E-M3TD

Uniarch



Features

- Uniarch
- Panda S Series
- PT WIFI IP Camera
- High image quality with 1/3" CMOS sensor and F1.6 aperture
- 3MP (2304x1296)@30/25fps
- Ultra 265, H.265, H.264
- Built-in microphone and speaker, support two-way audio, offer enhanced interaction
- Action touch: a physical button located on the top of the camera, supports call (one press) and privacy mode (double press).
- Human, vehicle, pet and baby cry detection
- IR night vision, up to 10 m IR distance
- White light, up to 10 m warm light distance
- Supports dual light mode: Switches between infrared and warm light automatically when preset is activated.
- Supports 512 Micro SD card of [%VAR%] GB
- Wi-Fi connection and easy installation

Specifications

Range	Uniarch
Image sensor	1/3" Progressive Scan CMOS
Maximum resolution	3 Megapixel (2304x1296)
Main Stream rate	3MP (2304*1296), Max 25fps; 2MP (1920*1080), Max 30fps; 720P (1280*720), Max 30fps;
Extra Stream rate	640*360,Max 30fps; 2CIF(704*288), Max 30fps; CIF(352*288), Max 30fps
Compression	Ultra H.265/H.265/H.264
WIFI	2.4G Wi-Fi (IEEE802.11b/g/n)
Lens	4 mm
Minimum illumination	0.02 Lux (Colour)
Infrared range	10 m
White light range	10 m
PTZ range	Pan 0° ~ 340°/ tilt-5° ~ 55°
Day / Night	Mechanical ICR filter
Internal memory	MicroSD card slot up to 512 GB
Autotracking	Yes
Intelligent detection	Human, vehicle, pet and baby cry detection
Alarms	Does not have
Audio	Includes microphone and speaker
Network interface	Ethernet 10/100 BaseT
Remote access	Web Browser, CMS Software (EZStation), Smartphone (EZView/EZLive)
Interoperability	ONVIF
Power	DC 5 V / 1.5 A
Led indicator	1: Red/Blue
Temp. operation	-10° C ~ 55° C

Dimensions

Ø80 x 121 (h) mm

Weight

180 g
