

RLS1100F (Rongta)

Terezi Rongta RLS1100F



Model	RLS1100F (Rongta)
Brend	NoBrand
Növ	Terezi

Specification

Capacity	Max capacity	6kg/15kg 15kg/30kg
	Min capacity	40g 100g
	Interval	2/5g 5/10g
	Accuracy class	III
Basic	COG	LCD 256X32
	SDRAM	8MB
	FLASH	16MB
	Ethernet	1 x RJ45
	Serial	1 x RS232
	Power source	1 x AC Jack
	Input	AC100V-240V 50/60Hz 1.5A
	Buttons	Hotkeys:112*2;Preset keys:28
	Notification	Buzzer
Dimension	433(L) x 372(W) x 506(H)mm	
Communication	Ethernet	TCP/IP 100M
	Wi-Fi(Optional)	IEEE 802.11 b/g/n;2.4GHz
Printer	Printing	Thermal print
	Print width	MAX 56mm
	Print speed	90 m/s
	Printer resolution	203 DPI
	Paper out	Auto peel off

Barcode format	2/5 interleaved, 128 EAN13 GS128	
Reliability requirements	Certification	OIML CE, Type evaluation, NTEP RLS1000 RLS1200
	Implementation standards	GB/T 7722-2020 OIML R 76-1(2006) and EN 45501:2015
Operation environment	Operating temperature	0 +40
	Operating humidity	20% 85%
	Storage temperature	-20 +60
	Operating temperature	5% 95%
Packaging material	Standard	Kraft paper Styrofoam
		Power cable Scale pan Warranty card Certificate User manual